



Product: [GUMXA06](#) 

Universal tight buffered fiber + CST distribution cable LSZH jacket 6f SM OS2 G.652.D & G.657.A1. CPR Eca.

Product Description

Universal (Indoor/Outdoor) tight buffered with Corrugated Steel Tape optical fiber distribution cable with Low Smoke Zero Halogen outer jacket. 6 fibers SM OS2 G.652.D & G.657.A1. CPR Euroclass Eca.

Technical Specifications

Product Overview

Suitable Applications:	For outdoor and indoor use in structured (data) wiring systems such as industrial backbone, campus backbone, building backbone (riser) and/or horizontal cabling. For outdoor and indoor use in networks for industrial, telecom, cable TV and/or broadcast. Support all computer network applications such as FDDI, Gigabit Ethernet and ATM.
------------------------	--

Fiber Specifications

Fiber Type:	OS2
Fiber Grade Acc to ITU-T:	G.652D & G.657A1
Fiber Buffer Material:	LSZH - Low Smoke Zero Halogen (Flame Retardant)
Fiber Buffer Construction:	Tight
Fiber Buffer Diameter:	0.9 mm
Fiber Count:	6
Fiber Color Coding:	TIA coding (Gxxxxxx.T): Blue, Orange, Green, Brown, Gray, White

Cable Construction

Cable Core Water Blocking:	Waterblocking Glass Yarns
----------------------------	---------------------------

Inner Jacket Specifications

Material:	LSZH - Low Smoke Zero Halogen (Flame Retardant)
-----------	---

Armor Specifications

Armor Type and Material:	CST - Corrugated Steel Tape
--------------------------	-----------------------------

Outer Jacket Specifications

Jacket Material:	LSZH - Low Smoke Zero Halogen (Flame Retardant)
Nom. Diameter:	11.0 mm (0.433 in)

Optical Characteristics

Wavelength	1310 nm	1550 nm	1625 nm
Max. Attenuation	0.40 dB/km	0.30 dB/km	0.30 dB/km

Mechanical Characteristics

Mechanical Tests

Description	Tested Standard	Requirement/Value	According to Family Specification
Cable Min. Bend Radius Installation (Short Term)	IEC 60794-1-21-E6	220 mm	IEC 60794-2-20
Cable Min. Bend Radius Operation (Long Term)	IEC 60794-1-21-E11	165 mm	IEC 60794-2-20
Cable Max. Tensile Strength Installation (Short Term)	IEC 60794-1-21-E1	1100 N (250 lbf)	IEC 60794-2-20
Cable Max. Tensile Strength Operation (Long Term)	IEC 60794-1-21-E1	370 N (83 lbf)	
Cable Max. Crush Resistance Installation (Short Term)	IEC 60794-1-21-E3	22 kN/m	IEC 60794-2-20

Cable Max. Crush Resistance Operation (Long Term)	IEC 60794-1-21-E3	11 kN/m	IEC 60794-2-20
---	-------------------	---------	----------------

Bulk Cable Weight:	101 kg/km (67.9 lbs/1000ft)
--------------------	-----------------------------

Temperature Range

Installation Temperature Range:	-5 °C to +50 °C
Operating Temperature Range:	-20 °C to +70 °C
Storage Temperature Range:	-30 °C to +70 °C

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor - Euroclass Eca
Flammability / Reaction to Fire:	IEC 60332-1-2, IEC 60332-3-22
CPR Compliance:	CPR Euroclass: Eca
ISO/IEC Compliance:	IEC 60794ISO/IEC 11801-1
European Halogen Free Standards:	IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3, IEC 61034-2 - Smoke Density Min. Transmittance = 60%
UK Regulation Compliance:	UKCA Mark

History

Update and Revision:	Revision Number: 0.257 Revision Date: 09-26-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
GUMXA06.002100	Black	Reel	2,100 m	8719605081490
GUMXA06.T02100	Black	Reel	2,100 m	8719605229632

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.